

Nimbus LED Surface Luminaire



Description

This stylish range of LED Surface Luminaires is available in both standard, microwave and emergency versions. Available in both white and chrome finish.

Features

- White or Chrome bezel with opal diffuser
- 14W SMD LED
- Lumen output 1200lm at 4000k
- Emergency mode lumen output 75lm
- Microwave sensor for reliable presence detection
- Low power consumption
- Emergency version uses Tridonic EM LED Driver
- 3 hour duration battery backup (emergency version)
- 3-year Guarantee

Technical Specification

Wattage	See range table
Voltage	230-240V 50Hz
Chip type	SMD
Lumen Output	1200lm
Emergency mode lumen output	75lm
CRI	>80
Colour temperature	4000K
Electrical classification	Class I
IP Rating	IP65

Range

14W LED Standard – White	L1055WH
14W LED Standard – Chrome	L1055CH
14W LED with Microwave sensor - White	L1052WH
14W LED with Microwave sensor - Chrome	L1052CH
14W LED Emergency version – White	L1058WH
14W LED Emergency version – Chrome	L1058CH

Dimensions

	Diameter	Depth
14W	340	105

All dimensions in mm

Standards

- BS EN 60598-1:2015
- BS EN 60529 (IP Rating)
- EN55015:2006+A1:2007+A2:2009
- EN61547:2009
- EN6100-3-2:2006+A1:2007+A2:2009
- LVD 2006/95/EC