

Smoke and Heat Alarms



Description

Range of mains powered optical smoke and heat alarms with advanced features. Alarms supplied with base making installation easier.

Satisfy all Grade D domestic requirements as laid down by BS 5839: Part 6 and the Building Regulations of England and Wales, Scotland and Northern Ireland.

Features

- Optical alarms are suitable for all circulation areas and habitable rooms, making it ideal for hallways and landings, as well as living rooms and bedrooms
- Heat alarms are designed for areas where fumes or dust may cause nuisance alarms, making it ideal for kitchens, attics and garages
- High visibility dust covers supplied to prevent dust ingress during building works
- Linkable up to 12 optical and heat alarms in total for larger properties
- Alarms have missing battery indicator and mechanism that prevents installation of the alarm if the battery is missing
- Supplied with mounting base that allows alarm to be pushed simply into place
- Mounting base has foam gasket built into mounting surface to prevent dust ingress
- Mounting base has large wiring space and fly lead electrical connection into alarm
- 5-year guarantee

Range

Optical Smoke Alarm	1163
Heat Alarm	1165

Technical Specification

Voltage	240Vac
Back up	DC 9V PP3 Alkaline
Sound Level	85dB at 3m
Operating Temp.	5°C to 38°C
Humidity	10% to 85% RH
Linkable*	Up to 12 units
Test Button	Yes
Silencer	Yes
Supply Indication	Green LED
Operation	Red LED
Heat Alarm Class	Class A2: 54-70°C

No user serviceable parts

* Not inter-linkable with legacy models 1111, 1113, 1115, 1151, 1153 or 1155

Standards

Optical	BS EN 14604:2008
Heat	BS 5446-2:2003