


Socket Outlets



Description

This uniquely shaped range of 10A architrave switches in the Deta Slimline style is easy to install, has clear white terminal markings and is supplied in individual protective bags.

This range of switches does not have to be de-rated for fluorescent loads and can be used for controlling lighting, door releases and bells.

Features

- Unique slim profile with curved top and bottom edges
- Concave rockers
- 3mm contact gap
- Only one size 4mm screwdriver needed
- Terminals have clearly embossed and white printed markings
- Grey font engraving
- Terminals have large lead-ins
- Fixing screw attached to rear of frontplate
- 25-year guarantee

Range

1g 1w 10A	S1320
1g 2w 10A	S1321
2g 2w 10A	S1322
1g push to make/break 2w 'press'	S1323
1g push to make 1w – bell symbol	S1323B

Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X rated
Contact gap	3mm
Plate size	85 x 34 x 7mm
Frontplate material	Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

Standards

- BS 60669-1:2000

Back Boxes

Minimum recommended depth

	Flush 25mm	Dry lining 35mm	Surface 25mm
1g	DB169	n/a	V1324
2g	n/a	n/a	V1325

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L	5	4	2	1