


Connection Units



Description

This uniquely shaped range is easy to install, with coloured terminals, clear white terminal markings and is supplied in individual protective bags.

This wide range includes flex outlet and neon versions.

Features

- Unique slim profile with curved top and bottom edges
- Concave rockers
- Only one size 4mm screwdriver needed
- Terminals have clearly embossed and white printed markings
- Colour coded terminals
- Neon versions available
- Neon leads enclosed
- Fuse carrier can be locked in the out position
- 2 earth terminals
- Most products have angled terminals to aid installation
- Terminals have large lead-ins
- 25-year guarantee

Technical Specification

| | |
|---------------------|-------------------|
| Voltage rating | 250Vac |
| Current Rating | 13A |
| Contact gap | 3mm |
| Frontplate material | Urea formaldehyde |

Urea flammability classification UL94 grade V-0

No user serviceable parts, except BS 1362 fuse links

Standards

- BS 1363 Part 4 : 1995+A4:2012
- Fuses – BS 1362

Range

| | |
|--|-------|
| Unswitched | S1360 |
| Unswitched, neon | S1361 |
| Unswitched, front flex outlet | S1362 |
| Unswitched, neon & front flex outlet | S1363 |
| Unswitched, bottom flex outlet | S1364 |
| Switched | S1370 |
| Switched, neon | S1371 |
| Switched, front flex outlet | S1372 |
| Switched, neon & front flex outlet | S1373 |
| Switched, bottom flex outlet | S1374 |
| DP switched, neon & bottom flex outlet | S1375 |
| Unswitched – 3A fuse | S1380 |
| Unswitched, neon – 3A fuse | S1381 |

Back Boxes

Minimum recommended depth

| | Flush 25mm | Dry lining 35mm | Surface 25mm |
|----|---------------|--------------------|-----------------|
| 1g | DB162 | DB2540 | V1221 |

Terminal Capacity

| | 2.5mm ² | 4mm ² | 6mm ² | 10mm ² |
|-------|--------------------|------------------|------------------|-------------------|
| L & N | 4 | 3 | 2 | 1 |