


## Connection Plates



### Description

This uniquely shaped, easy to install, range is designed to match the Deta Slimline range of accessories. With coloured terminals, each product is supplied in individual protective bags.

### Features

- Unique slim profile with curved top and bottom edges
- Only one size 4mm screwdriver needed
- Colour coded terminals
- Dual terminals of live, neutral and earth
- Large terminal capacity
- 25-year guarantee

### Technical Specification

Voltage rating            250Vac  
 Current Rating            25A  
 Frontplate material        Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

### Standards

- BS 5733 : 2010+A1:2014

### Range

1g blank connection plate	S1200
2g blank connection plate	S1201
25A connection plate with flex outlet	S1215
25A connection plate, no flex outlet	S1216
45A cooker cable outlet	S1217

### Back Boxes

Minimum recommended depth

	Flush 25mm	Dry lining 35mm	Surface 25mm
1g	DB162	DB2540	V1221
	47mm	46mm	46mm
S1217	DB167	DB2542	V1228

### Terminal Capacity

	2.5mm <sup>2</sup>	4mm <sup>2</sup>	6mm <sup>2</sup>	10mm <sup>2</sup>
L & N	5	3	2	1