


## Plateswitches



### Description

This uniquely shaped range of 10A light switches is easy to install, has clear white terminal markings and is supplied in individual protective bags.

This range of plateswitches do not have to be de-rated for fluorescent loads and can be used by controlling lighting, door releases and bells.

### Features

- Unique slim profile with curved top and bottom edges
- Concave rockers
- Only one size 4mm screwdriver needed
- Terminals have clearly embossed and white printed terminals
- Grey font engraving
- Terminals have large lead-ins
- Range can be expanded using Gridswitch range
- 25-year guarantee

### Range

1g 1w 10A	S1202
1g 2w 10A	S1203
2g 2w 10A	S1204
3g 2w 10A	S1205
4g 2w 10A	S1244
6g 2w 10A	S1245
Intermediate 10A	S1246
3 pole fan isolator 10A	S1247
Push to make/break 2w 'press'	S1249
Push to make/break 2w – bell symbol	S1249B
Neon Locator Plate – white neon	S1417WH
Door card switch, energy saving	S1248
2 Gang 2 Way + Intermediate	S1325

### Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X Rated
Contact gap	3mm
Frontplate material	Urea formaldehyde

Urea flammability classification UL94 grade V-0

No user serviceable parts

### Standards

- BS 60669-1:2000

### Back Boxes

Minimum recommended depth

	Flush	Dry lining	Surface
	25mm	35mm	25mm
1-3g	DB152	DB2540	V1220/E
4-6g	DB163	DB2541	V1223

### Terminal Capacity

	2.5mm <sup>2</sup>	4mm <sup>2</sup>	6mm <sup>2</sup>	10mm <sup>2</sup>
L	5	4	2	1