Connection Units



Description

This uniquely styled range is easy to install, with clear white terminal markings and is supplied in individual display boxes.

Features

- Black or white inserts available
- Concaved rockers
- 1.5mm thick front plates
- Protective film on frontplates
- Only one size 4mm screwdriver needed
- Grey font engraving
- Discreet neons
- Neon leads enclosed
- Fuse carrier can be padlocked in the out position (not supplied)
- Colour coded terminals
- Clear white terminal markings
- 2 earth terminals
- Terminals have large lead-ins
- 25-year guarantee

Range

Unswitched spur	8141
Switched spur	8142
Switched spur with neon	8143
Switched spur with flex outlet and neon	8144

Prefix finish with

Chrome	CH
Satin Chrome	SC
Black Nickel	BN
White or Black inserts	W or B

Technical Specification

Voltage rating	250Vac
Current Rating	13A
Contact gap	3mm

No user serviceable parts, except BS 1362 fuse links

Back Boxes

Minimum recommended depth

	Flush 35mm	Dry lining 35mm
1g	DB164	DB2540

Standards

- BS 1363 Part 4 : 1995
- Fuses – BS 1362

Terminal Capacity

	2.5mm²	4mm²	6mm²	10mm²
L & N	4	3	2	1

Deta Electrical Company Ltd.
Kingsway House Laporte Way
Luton Bedfordshire LU4 8RJ UK
Tel. +44 1582 544 548 technical@detaelectrical.co.uk