


Connection Plates



Description

This uniquely styled range is easy to install, with clear white terminal markings and is supplied in individual display boxes.

Features

- Black or white inserts available
- 1.5mm thick front plates
- Metal capped rockers
- Grey font engraving
- Discreet neon
- Neon leads enclosed
- Fuse carrier can be padlocked in the out position
- Only one size 4mm screwdriver needed
- Colour coded terminals
- Clear white terminal markings
- Terminals have large lead-ins
- Protective film on frontplates
- 25-year guarantee

Technical Specification

Voltage rating 250Vac
 Current Rating 13A
 Contact gap 3mm

No user serviceable parts, except BS 1362 fuse links

Standards

- BS 1363 Part 4 : 1995
- Fuses – BS 1362

Range

Unswitched spur	8141
Switched spur	8142
Switched spur with neon	8143
Switched spur with flex outlet and neon	8144
1g blank plate	8161
2g blank plate	8162

Prefix finish with

Chrome	CH
Satin Chrome	SC
Black Nickel	BN
White or Black inserts	W or B

Back Boxes

Minimum recommended depth

	Flush 35mm	Dry lining 35mm
1g	DB164	DB2540

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L & N	4	3	2	1