


Plateswitches



Description

This uniquely styled range has concealed screws behind a smooth frontplate with an ultra slim profile.

Features

- All plate switches are x-rated and can be used for switching inductive or fluorescent loads with de-rating
- Metal frontplates
- Concave rockers
- Only one size 4mm screwdriver needed
- Clear white markings
- Terminals have large lead-ins
- 25-year guarantee

Range

10A 1 gang 2-way plate switch	8501
10A 2 gang 2-way plate switch	8502
10A 3 gang 3-way plate switch	8503
10A 4 gang 4-way plate switch	8504
10A intermediate plate switch	8506
10A 3 pole fan isolator switch	8507

Suffix finish with

Chrome	CH
Satin Chrome	SC
Black Nickel	BN
White	WH
White or Black inserts	W or B

Technical Specification

Voltage rating	250Vac
Current Rating	10A
	X Rated
Contact gap	3mm

No user serviceable parts

Standards

- BS 60669-1:2000

Back Boxes

Minimum recommended depth

	Flush 25mm	Dry lining 35mm	Surface 25mm
1-3g	DB152	DB2547	V1220
4g	DB163	DB2548	V1223

Terminal Capacity

	2.5mm ²	4mm ²	6mm ²	10mm ²
L	5	4	2	1